

# Telebelt®

Export Models



1



TB 110G mounted on a Mercedes-Benz chassis shown.  
Also available: Iveco, Mack Low Profile, Sterling and TOR chassis.

- Places material from sand to 100mm rock
- Smooth surge-free conveying results
- Sets up under low ceiling heights
- Superior reach and versatility

## Unique Outrigger Design





## A Full Line of Proven Telebelt® Performers



### TB 80

- 24.38m horizontal reach
- Three-section telescopic boom is controlled by a single joystick on the remote control
- 275m<sup>3</sup>/hr maximum outputs
- 457mm belt width
- Handles 0mm to 305mm concrete slump
- Places materials from sand to 100mm rock
- Sets up under low 4.50m heights
- Front and rear outriggers hydraulically rotate out and down to a compact 5.20m footprint



### TB 110G

- 32.34m horizontal reach
- Four-section telescopic boom is controlled by a single joystick on the remote control
- 275m<sup>3</sup>/hr maximum outputs
- 457mm belt width
- Handles 0mm to 305mm concrete slump
- Places material from sand to 100mm rock
- Sets up under low 4.80m heights
- Outriggers hydraulically extend out and down



### TB 130

- 38.56m horizontal reach
- Five-section telescopic boom is controlled by a single joystick on the remote control
- 275m<sup>3</sup>/hr maximum outputs
- 457mm belt width
- Handles 0mm to 305mm concrete slump
- Places material from sand to 100mm rock
- Sets up under low 4.70m heights
- Outriggers hydraulically extend out and down

Models may only be available on certain chassis. Please contact your Putzmeister representative for available mounting configurations and options.



Putzmeister AG  
Max-Eyth-Str. 10  
D-72631 Aichtal  
Telephone (0 71 27) 599 - 0  
Facsimile (0 71 27) 599 - 520  
www.putzmeister.de



Authorized Distributor

10